

American Linear Collider Workshop



Highlights from the American Linear Collider Workshop 2003

Fulvia Pilat

CAD Seminar, July 24 2003



Outline

- > Brief intro/primer to LC projects
- > ALCW workshop
- > IR/beam delivery session
- > Accelerator physics and simulation session
- > BNL based LC activity
- > The international 'roadmap' towards LC



LC Primer

- □ A 500 GeV c.m. linear collider with an upgrade path to 1
 TeV has been endorsed by HEPAP as the central project for High Energy Physics in the 2002 'roadmap' document following Snowmass 2001
- ☐ 3 LC projects exist worldwide:

GLC/NLC warm RF technology (SLAC/KEK)


TESLA SC RF technology (DESY)

CLIC two-beam powering scheme (CERN)

"US cold option" Tesla-NLC hybrid that morphs the Tesla DR and main linac to the NLC beam delivery system (crossing angle, compact FF optics) studies to allow the "technology choice" - warm vs. cold RF - to be on equal footing. (by ~mid 2004)




GLC/NLC (former JLC/NLC)



Fulvia Pilat, American Linear Collider Workshop 2003




NLC RF (simplified)





NLC RF schematics

(One of ~2000 at 500 GeV cm, One of ~4000 at 1 TeV cm)



Eight Accelerator Structures (0.6 m, 65 MV/m Unloaded, 52 MV/m Loaded)



NLC RF structures - development




(65 MV/m Unloaded Gradient Goal for 0.5 & 1 TeV Collider)

Making Steady Process Toward an 'NLC/JLC – Ready' Structure

- During Past Year Operated a Structure at 90
 MV/m with an Acceptable Trip Rate (< 0.1/hr).
- Currently Developing Structures with Suitable Average Iris Radii from a Wakefield Perspective.
- Recent Structures Include Slots for Wakefield Damping.

53 cm Traveling-Wave Structure




Fulvia Pilat, American Linear Collider Workshop 2003



NLC RF structures - performance


Breakdown Rates at 400 ns Pulse Width



Fulvia Pilat, American Linear Collider Workshop 2003




Tesla: sc cavities







Electro-polishing for 35 MV/m

- EP developed at KEK by Kenji Saito (originally by Siemens)
- Coordinated R&D effort: DESY, KEK, CERN and Saclay








Electro-polishing (EP) instead of the standard chemical polishing (BCP) eliminates grain boundary steps — Field enhancement.

Gradients of 40 MV/m at Q values above 10^{10} are now reliably achieved in single cells at KEK, DESY, CERN, Saclay and TJNAF.



TESLA 800 Performances


Vertical Tests






TESLA 800 in Chechia Long Term (> 600 h) Horizontal Tests

- In Chechia the cavity has all its ancillaries
- Chechia behaves as 1/8th (1/12th) of a TESLA cryomodule






US "cold option"



Fulvia Pilat, American Linear Collider Workshop 2003



Beam Delivery System - optics design



A TESLA linac lattice is matched into an unmodified NLC beam delivery system via a ~200m matching section.

The NLC beam delivery system is then adjusted to give TESLA lattice functions at the IP using the matching section. β *x,y= 15, 0.4 mm at IP

This matching section is then used for the **fast extraction** (beam abort/tune-up line) system.

2 separate dumps per beam



Cold option reference design

major changes made to the TESLA design are:
☐ An increase in the upgrade energy to 1 TeV (c.m.), with a tunnel of
sufficient length to accommodate this in the initial baseline, assuming a 35
MV/m gradient.
☐ Use of the same injector beam parameters for the 1 TeV (c.m.) upgrade
as for 500 GeV (c.m.) operation
□ The choice of 28 MV/m as the initial main linac design gradient for the 500
GeV (c.m.) machine
☐ The use of a two-tunnel architecture for the linac facilities.
□ An expansion of the spares allocation in the main linac
$\Box A$ re-positioning of the positron source undulator to make use of the 150 GeV
electron beam, facilitating operation over a wide range of collision energies
from 91 to 500 GeV
The adoption of an NLC-style beam delivery system with superconducting
final focus quadrupoles, which accommodates both a crossing angle and
collision energy variation
□At the subsystem and component level, specification changes to
facilitate comparison with the warm LC option.



Major ALCPG Meetings/Workshops since Fall 2002

	LCDsoft	NIU	Nov 7-9
•	γ collider		
	workshop	SLAC	Nov 21-22
•	LHC/LC	Fermilab	Dec 12-13
•	ALCPG	UT-Arlington	Jan 9-11 🐳
•	LoopfestII	Brookhaven	May 14-16
•	LC Sim Wkshp	SLAC	May 19-22
•	ALCPG	Cornell	Jul 13-16 CORNELL

...and many other WG meetings (see the WG web pages and talk to the WG leaders)



IR/Beam Delivery WG

Accelerator Working Group: Beam Delivery & IR

Tuesday, July 15, 8:30-10:30 a.m.

8:30-8:55	Overview of IR & BDS issues	Tom Markiewicz
8:55-9:25	Collimation and Second IR for NLC	Andrei Seryi
9:25-9:45	Status and plans for linear colliders R&D in UK	Philip Burrows
9:45-10:10	The compact superconducting final focus doublet option	Brett Parker
10:10-10:30	Vibration and stabilization	Richard Partridge

Conveners: F. Pilat, BNL T. Mattison, UBC



"editorial" comments

IR designs are converging

- projects adopting, or at least considering, ideas from other designs:
- optics, crossing angle, super-conducting quads, vibration, collimation
- Eternal questions remain (there are no solutions, only decisions.....) → trade-offs:
- □ machine luminosity vertex detector radius
- detector acceptance and access machine components and supports



IR Issues

(Markiewicz)

- Crossing Angle
 - Crab Cavities
 - Beam Extraction
- Physics & Detector
 - Beam Pipe Radius @ IP
 - Solenoid Field
 - Detector Access Model
 - Energy Flexibility
- Backgrounds
 - Detector Masking
 - Heat / Radiation

Final Doublet Support

- Support Tube
 - · Cantilevered
 - · Across IP
- Vibration Control
 - Inertial Feedback
 - Optical Feedback
 - Feed-forward
- Beam-Beam Feedback
 - · Intra-train
 - 120 Hz
- Machine Diagnostics
 - Luminosity
 - Energy
 - Polarization




Second IR

Possible to achieve very comparable luminosity, over wide energy range

Design strategy: lengthen the 2nd IR BDS (several design iterations) – reduce SR $\delta\epsilon/\epsilon$ in the big bends

Seryi



Fulvia Pilat, American Linear Collider Workshop 2003




Backgrounds

control with:

- > Large apertures
- > beam collimators
- > radiation shields
- > muon spoilers

ILC-TRC: designs are an existence proof that solutions exist





Vibrations/stabilization

Vibrations of final quads

(Markiewicz, Partridge, Burrows)

- Feedback using beam-beam deflection + steering everyone uses it for slow drifts (many seconds)

 TESLA can do it bunch by bunch tests of nanosecond bunch feedback at NLCTA
- Stabilization: quad position measurement and control feedback SLAC: 6-axis feedback of block on springs with accels + electrostatic quad and support mockup feedback project specialized accelerometer R&D
- Rigid support tube across IP

 KEK comparing finite-element calcs to simple cantilever & span geometries building 1/10 scale support tube prototype



Quad&support mockup FBK

Partridge



Fulvia Pilat, American Linear Collider Workshop 2003



Compact SC FF doublet

Parker

Planned: warm field quality measurements, cold quench tests

BNL LDRD Accomplishments & Areas of Ongoing Development

First made small diameter singlelayer (HERA-II) coils with desired features. Then went on to short double-layer windings.





Next wound 1m

coils (see above) & found stylus pressure bows tube. Now making 2m coils with mid-point support (right).



Superconducting

Magnet Division




Figure 6.3: Superconducting Final Focus Magnet Layout Schematic

Linear+nonlinear FF corrector layers (operational experience at RHIC positive for skew quad, sextupole and octupole correction)

Cryostat Outer Surface Heat Shield Vertical Support Horizontal Support Single Strand Conductor Seven Strand Cable G10, S-Glass & Epoxy LHe Flow Space Coil Support Tubes

Figure 6.4: Superconducting QD0 Design Schematic

Superconducting Final focus-BNL design

144 T/m @ 250 GeV Aperture 20 mm




SC FF doublet stabilization

Parker

First Superconducting Magnet Vibrations Studies at BNL Magcool NATIONAL LABORATORY Superconducting Magnet Division Magnet Division





- · Some equipment is now available (see photos).
- · Thinking about how to do cold measurements.
- But still just getting started.

From RHIC BPM data (triplet cryo vibration): ~200 nm (horizontal) ~0 nm (vertical)

- >Plans for measurements on cryostats and then cold masses
- ➤ Vigorous R&D on vibration and stabilization of SC magnets necessary, needs:

RESOURCES (\$)
COLLABORATION



LC Program in UK (Burrows)

Accelerator Science & Technology Centre established in 2000

\$4M seed money for FY00-03 from PPARC + UK labs for ASTeC + universities

8 accel-related projects, 18 FTEs incl 6 students in collab with offshore labs

no time to summarize them

\$14M for **FY04-05**, perhaps \$17M for FY04-06, for accelerator science, "bulk" for LC

PPARC LC steering group: focus on beam delivery and machine-detector interface

Goal is to ramp up to ~10% UK contribution to LC project (Phil says the Queen has still to sign on that though....©)



Simulation/Dynamics WG

Accelerator Working Group: Beam Dynamics and Accelerator Simulation I

Sunday, July 13, 1:00-3:00 p.m.

1:00-1:20	UCLC Progress Report: Accelerator Physics Research at NIU, July, 2002 - July, 2003	Court Bohn
1:20-1:40	UCLC Progress Report: Beam Simulation (ppt pdf)	David Rubin
1:40-2:20	Reliability and Operations Modeling of a Linear Collider (ppt pdf)	Tom Himel
2:20-3:00	Emittance Tuning: Details, Details, (ppt pdf)	Peter Tenenbaum

Accelerator Working Group: Beam Dynamics and Accelerator Simulation II

Tuesday, July 15, 10:55 a.m. -12:55 p.m.

10:55-11:15 LCRD Progress Report: Low-Emittance Electron Beams for Wakefield Measurements (ppt pdf)	John Power
11:15-11:35 UCLC Progress Report: Update on the Usability of Spent Beams for Physics Experiments at the Linear Collider	Sekazi Mtingwa
11:35-12:15 Simulation of Damping Ring Issues	Andy Wolski
12:15-12:55 Simulation Techniques	Andrei Seryi

Conveners: Raubenheimer, Poling



LC simulations/dynamics

```
> Object
Performance → peak luminosity (PT, Seryi)
Reliability \rightarrow integrated luminosity (Himel)
> Level of detail
More physics (Wolski: wiggler in DR, Bohn: space charge)
Integration (Seryi: DR-to-IP, 2 beams, GM BB FBK..→luminosity)
> Validation
'building blocks' (Seryi > collimator wake measurements vs.model)
X-checks, benchmarking of different codes (Seryi, ILC-TRC)
> Widening LC dynamics/simulation community
LC simulation environment setup
                                   (Rubin - Cornell, UK, BNL...)
Simulation results database
                                   (Burrows)
```



Reliability simulation (Himel)

Pre#minary results: cold machine					
%	access	#	energy		
time	per	tun-	over-	MTBF	
down	month	nels	head	fudge spe	ecial conditions
25.3	2.9	2	2%	1_	Double tunnel
45.4	14.1	1	2%	1	Double fullier
39.6	12.1	1	4%	1	
36.9	10.1	1	2%	10 🕶	Increase MTBF
26.8	6.4	1	4%	10	1:00
27.0	6.1	1	4%	10	different seed
13.6	3.4	2	2%	1 🔸	Decrease
24.7	2.9	2	2%	1	tuning time
19.8	3.3	2	2%	1	Taring Tillo
15.6	2.3	2	4%	10	

- >Write a simulation that given the MTBFs, MTTRs, components access requirements for repair can calculate availability & integrated luminosity
- >Collect component data in existing machines for guidance
- ➤ Iterate as many times as we have time to minimize the overall cost of the LC while maintaining the goal availability

- Different methodology (Tesla):
- FMEA (Failure Mode Effect Analysis)
- → identify <u>critical components</u>

- □Interesting for existing machines
- □Potential for assessing machine availability during commissioning phase



The devil is in the details (PT)


- Emittance growth from DFS Tesla
- Effect of jitter in NLC DFS
- > Emittance growth in NLC bypass line.....
- □ necessary to include details:
- jitters, drifts, RF trips and deflections and especially interaction with **feedback loops**
- ☐ Tuning simulation on signals that will be available in control room
- → Will be necessary to carefully develop a commissioning strategy



DR => IP <= DR integrated simulation tools



ILC-TRC




DIMAD - in Bunch Compressor and Beam Delivery System (high order optics, accurate particle tracking)

- in Linac (wakes, fast tracking of macroparticles) LIAR

GUINEAPIG - beam-beam collisions at IP

PLACET or MERLIN - in either BC, Linac or BDS

MATLAB driven





Virtual NLC?

1 bunch, 500 pulses takes 10 hours on 2GHz PC (and this is with quite limited physics included)

Real time calculations (120Hz, 192 bunch/train) will require: 300000 of 11.46Hz ideally parallel processors



If each of them is 1cm long, they will span over 3km





The bodies

LCRD

UCLC

ALCPG

USLCSG

DOE

NSF

WorldWideStudy

ILCSC


ICFA

ACFA

ECFA




Does this remind you of Scrabble?





Scrabble and the Linear Collider





US Regional Structure

US Linear Collider Steering Group (J. Dorfan)

Physics and Detectors Subcommittee

American Linear Collider Physics Group

http:blueox.uoregon.edu/~lc/alcpg

Detector and Physics Simulations:

N Graf/M Peskin

Vertex Detector:

J. Brau /N. Roe/M Battaglia Trackina:

B Schumm/D. Karlen/K, Riles

Particle I.D.:

B. Wilson

Calorimetry:

R. Frey/A. Turcot/D. Chakraborty

Muon Detector:

G. Fisk

DAcq, Magnet, and Infrastructure:

U. Mallik

Interaction Regions, Backgrounds:

T. Markiewicz/S. Hertzbach IP Beam Instrumentation:

M. Woods /E. Torrence/D. Cinabro

LHC/LC Study Group

- chaired by H. Schellman/F. Paige

Working Group Leaders

Co-chairs: Jim Bray and Mark Oreglia

Executive Committee

F Blucher D Gerdes

L. Gibbons D. Karlen

Y-K Kim H. Murayama

J. Richman R. VanKooten Higgs:

R. Van Kooten/M. Carena/H. Haber SUSY:

U. Nauenberg/J. Feng /F. Paige

New Physics at the TeV Scale and Beyond:

J. Hewett/D. Strom/S. Tkaczyk

Radiative Corrections (Loopverein):

U. Baur/S. Dawson/D. Wackeroth Top Physics, QCD, and Two Photon:

Lynne Orr/Aurelio Juste

UCLC and LCRD

D. Amidei, G. Dugan, Jeff

e-e-:

Precision 8

Graha

G. Gollin, J. Jaros,

U. Mallik, R. Patterson, <u>Liaison to accel. R&D</u> T. Himel, D. Finley, J. Ro

J. Rogers, S. Tkaczyk

Global Detector Network Testbeams G. Fisk, J. Yu M. Hildreth/R. Van Kooten

Accelerator Subcommittee chair: G. Dugan

International Subcommittee chair: M. Tigner

\$ ©





Canadian support as well





World-wide Structure

International Linear Collider Steering Committee (established 2002) (M. Tigner)

Physics and Detectors Subcommittee

Organizing Committee of the World-wide Study of Physics and Detectors for Future Linear e+e- Colliders (est. 1998, ICFA)

- J. Brau, D. Miller, H. Yamamoto, co-chairs (past co-chairs C. Baltay, S. Komamiya)
- Coordinates three regional studies
- ·Organizes LCWS (Paris, April 19-23,2004)
- ·Fills subcommittee role to ILCSC

Accelerator Subcommittee Greg Loew, chair

Parameters
Subcommittee
Rolf Heuer, chair

Communications
Subcommittee
N. Calder et al


ACFA Joint Linear Collider
Physics and Detector Working Group



American Linear Collider

Physics Group







The international 'roadmap' to LC

Snowmass (2001) and HEPAP endorsement ILCSC/accelerator subcommittee (Loew) issued a comprehensive report overviewing and comparing the designs of NLC/JLC, Tesla, CLIC (2002) □ Development of a "cold option" for fair comparison to the "warm option" (2003) □ Technology choice - ILCSC (Tigner) - mid 2004 (committee) of 'wise-persons') ☐ Establish an international design group (2004-2005) □ Produce a CDR (2005) □ Produce a TDR (2007) Approval & begin construction (target 2009) □ Commissioning (target 2014)



Conclusions (from Jim Brau)

- We are making good progress on many fronts
- We are getting support for university R&D, making possible a real start on the detector and machine R&D
- · We have a long way to go
- Keep up the charge



